Thermoelectric Materials with the Skutterudite Structure: New Results

Jean-Pierre Fleurial, Thierry Caillat and Alex Borshchevsky Jet Propulsion laboratory/California Institute of I'ethnology 4800, Oak Grove Drive, MS 277-212, Pasadena, CA91109 %? 818-354-4144 Fax 818-393-69S 1

New experimental findings on semiconductors with the relatively complex 32 atom unit cell skutterudite crystal structure show that these materials possess attractive transport properties and have a good potential for achieving ZT values larger than for state-of-the-art thermoelectric materials. Both n-type and p-type conductivity samples have been obtained, using several preparation techniques. Associated with a low hole effective mass, very high carrier nobilities, low electrical resistivities and moderate Seebeck coefficients are obtained in p-type skutterudites. For a comparable doping level, the carrier nobilities of n-type samples were found to be about an order of magnitude lower than values of p-type samples. However, the much larger electron effective masses and Seebeck coefficients make n-type skutterudites even more promising candidates. "I'he thermal conductivities of the binary skutterudite compounds at high temperatures are comparable to the values obtained for Si-Ge alloys, but are too large to be useful for thermoelectric applications at lower However, in addition to literature results, a large number of isostructural compounds, solid solutions and related phases have been discovered. These skutterudite compositions offer many possibilities for substantially reducing the lattice thermal conductivity and for optimizing the electrical properties to a specific temperature range of thermoelectric applications. An overview of recent results is provided and current approaches to experimentally achieving high ZT in skutterudite materials are discussed in this paper.